




SS6900系列 ( SS6900 SERIES )



Seal(RS)



Shield(Z)



Open

单位 ( unit ) :mm

| 型号<br>BearingNO. | 内径<br>Bore | 外径<br>O.D | 宽度Width             | 基本额定载荷(KH)<br>Load Rating |      | 钢球 Ball |       | 倒角<br>Rmin | 重量<br>Weight<br>(KG) |
|------------------|------------|-----------|---------------------|---------------------------|------|---------|-------|------------|----------------------|
|                  |            |           | Sheld/Seal<br>/Open |                           |      |         |       |            |                      |
|                  |            |           |                     | Cor                       | Cr   | NO.     | Size  |            |                      |
| SS6900           | 10         | 22        | 6                   | 1.3                       | 2.7  | 9       | 3.175 | 0.3        | 0.008                |
| SS6901           | 12         | 24        | 6                   | 1.5                       | 2.9  | 10      | 3.175 | 0.3        | 0.008                |
| SS6902           | 15         | 28        | 7                   | 2.3                       | 4.3  | 10      | 3.969 | 0.3        | 0.012                |
| SS6903           | 17         | 30        | 7                   | 2.6                       | 4.6  | 11      | 3.969 | 0.3        | 0.014                |
| SS6904           | 20         | 37        | 9                   | 3.7                       | 6.4  | 11      | 4.763 | 0.3        | 0.031                |
| SS6905           | 25         | 42        | 9                   | 4.5                       | 7.0  | 12      | 4.763 | 0.3        | 0.038                |
| SS6906           | 30         | 47        | 9                   | 5.0                       | 7.2  | 14      | 4.763 | 0.3        | 0.043                |
| SS6907           | 35         | 55        | 10                  | 6.8                       | 9.5  | 13      | 5.953 | 0.6        | 0.078                |
| SS6908           | 40         | 62        | 12                  | 9.9                       | 13.7 | 13      | 6.747 | 0.6        | 0.103                |
| SS6909           | 45         | 68        | 12                  | 10.9                      | 14.1 | 14      | 6.747 | 0.6        | 0.123                |
| SS6910           | 50         | 72        | 12                  | 11.7                      | 14.5 | 15      | 6.747 | 0.6        | 0.122                |
| SS6911           | 55         | 80        | 13                  | 13.2                      | 15.9 | 16      | 6.747 | 1.0        | 0.170                |
| SS6912           | 60         | 85        | 13                  | 14.2                      | 16.4 | 18      | 6.747 | 1.0        | 0.181                |